

Aviora SM 595x595

Surface mounted

SPECIFICATIONS

Colour	Matt white RAL 9016 (=MW)
Beam angle (FWHM)	Standaard 85° (100° FWTM) / On request 75° (95° FWTM)
UGR (4H8H 70/50/20)	<19
Fixture material	Housing: Steel / Reflector glass: Polycarbonate
Environment	Indoor
IK rate	IK03
Operating temperature (Ta)	-20°C / +45°C
Safety marks	EN60598 / EN62031 / EN 62471
EMC compliance	EN55015
Colour consistency (SDCM)	MacAdam step 3
Warranty	7 years * (within the European Union and the countries of the Free Trade Association for products delivered after 1 May 2015)
Energy class	A+

This luminaire contains built-in LED lamps. There are no exchangeable parts inside the luminaire. EU 874/2012



IP20

ITEM SPECIFICATIONS (PART A)

Description	Item code	Extra	Input	W	Lm	Lm/W	CRI (typ.)	UGR	Pf	Ripple	Inrush current	B-16A Fuse
Aviora SM 595x595 595x595 4100 Lm 3000K No dim	3CED03MWF202	Incl. PSU	220-240V	37,3	4100	110	83	15.7	0.98	<3%	5A 50µS	50 pcs
Aviora SM 595x595 4100 Lm 3000K 1-10V & Push	3CED03MWG202	Incl. PSU	220-240V	37,3	4100	110	83	15.7	0.95	<3%	5A 50µS	50 pcs
Aviora SM 595x595 4100 Lm 3000K Dali	3CED03MWH202	Incl. PSU	220-240V	37,3	4100	110	83	15.7	0.95	<3%	5A 50µS	50 pcs
Aviora SM 595x595 5350 Lm 3000K No dim	3CEE03MWF202	Incl. PSU	220-240V	56,0	5350	96	83	16.6	0.95	<3%	20A 400µS	15 pcs
Aviora SM 595x595 5350 Lm 3000K 1-10V & Push	3CEE03MWG202	Incl. PSU	220-240V	56,0	5350	96	83	16.6	0.95	<3%	20A 400µS	15 pcs
Aviora SM 595x595 5350 Lm 3000K Dali	3CEE03MWH202	Incl. PSU	220-240V	56,0	5350	96	83	16.6	0.95	<3%	20A 400µS	15 pcs
Aviora SM 595x595 4350 Lm 4000K No dim	3CED03MWF302	Incl. PSU	220-240V	37,3	4350	117	83	15.9	0.98	<3%	5A 50µS	50 pcs
Aviora SM 595x595 4350 Lm 4000K 1-10V & Push	3CED03MWG302	Incl. PSU	220-240V	37,3	4350	117	83	15.9	0.95	<3%	5A 50µS	50 pcs
Aviora SM 595x595 4350 Lm 4000K Dali	3CED03MWH302	Incl. PSU	220-240V	37,3	4350	117	83	15.9	0.95	<3%	5A 50µS	50 pcs
Aviora SM 595x595 5650 Lm 4000K No dim	3CEE03MWF302	Incl. PSU	220-240V	56,0	5650	101	83	16.8	0.95	<3%	20A 400µS	15 pcs
Aviora SM 595x595 5650 Lm 4000K 1-10V & Push	3CEE03MWG302	Incl. PSU	220-240V	56,0	5650	101	83	16.8	0.95	<3%	20A 400µS	15 pcs
Aviora SM 595x595 5650 Lm 4000K Dali	3CEE03MWH302	Incl. PSU	220-240V	56,0	5650	101	83	16.8	0.95	<3%	20A 400µS	15 pcs

ITEM SPECIFICATIONS (PART B)


Description	Safety class	Energy class	Weight	Dimensions single carton	Quantity per pallet	Expected lifespan (25°C)		
						L70B50	L80B50	L90B50
Aviora SM 595x595 4100 Lm 3000K No dim	II	A+	8235 gr	605x605x90 mm	66 pcs	134.000 hrs	82.000 hrs	37.000 hrs
Aviora SM 595x595 4100 Lm 3000K 1-10V & Push	II	A+	8235 gr	605x605x90 mm	66 pcs	134.000 hrs	82.000 hrs	37.000 hrs
Aviora SM 595x595 4100 Lm 3000K Dali	II	A+	8235 gr	605x605x90 mm	66 pcs	134.000 hrs	82.000 hrs	37.000 hrs
Aviora SM 595x595 5350 Lm 3000K No dim	II	A+	8235 gr	605x605x90 mm	66 pcs	134.000 hrs	82.000 hrs	37.000 hrs
Aviora SM 595x595 5350 Lm 3000K 1-10V & Push	II	A+	8235 gr	605x605x90 mm	66 pcs	134.000 hrs	82.000 hrs	37.000 hrs
Aviora SM 595x595 5350 Lm 3000K Dali	II	A+	8235 gr	605x605x90 mm	66 pcs	134.000 hrs	82.000 hrs	37.000 hrs
Aviora SM 595x595 4350 Lm 4000K No dim	II	A+	8235 gr	605x605x90 mm	66 pcs	134.000 hrs	82.000 hrs	37.000 hrs
Aviora SM 595x595 4350 Lm 4000K 1-10V & Push	II	A+	8235 gr	605x605x90 mm	66 pcs	134.000 hrs	82.000 hrs	37.000 hrs
Aviora SM 595x595 4350 Lm 4000K Dali	II	A+	8235 gr	605x605x90 mm	66 pcs	134.000 hrs	82.000 hrs	37.000 hrs
Aviora SM 595x595 5650 Lm 4000K No dim	II	A+	8235 gr	605x605x90 mm	66 pcs	134.000 hrs	82.000 hrs	37.000 hrs
Aviora SM 595x595 5650 Lm 4000K 1-10V & Push	II	A+	8235 gr	605x605x90 mm	66 pcs	134.000 hrs	82.000 hrs	37.000 hrs
Aviora SM 595x595 5650 Lm 4000K Dali	II	A+	8235 gr	605x605x90 mm	66 pcs	134.000 hrs	82.000 hrs	37.000 hrs

All values are measured at 230V (+/- 7%)

CHOOSE YOUR LUMEN OUTPUT

Item	mA	W	Lumen Output		Lumen / Watt	
			3000K	4000K	3000K	4000K
Special request	500	26.6	3200	3400	120	128
Special request	550	29.3	3500	3750	119	128
Standard	700	37.3	4100	4350	110	117
Special request	900	47.5	5000	5300	105	112
Standard	1050	56.0	5350	5650	96	101

DIMENSIONS



BACKSIDE

