

REWARDING BRIGHTNESS




Sensor

SensorLinea 75

Fixed

Specifications

| | |
|----------------------------|-----------------------------|
| Colour white | Matt white RAL 9016 (XX=MW) |
| Colour black | Matt black RAL 9005 (XX=BL) |
| Beam angle (FWHM) | 24° / 60° |
| Fixture material | Die cast aluminium |
| Environment | Indoor |
| IP rate | IP20 |
| IK rate | IK03 |
| Operating temperature (Ta) | -20°C / +45°C |
| Safety marks | EN60598 / EN62031 / EN62471 |
| EMC compliance | EN55015 |
| Colour consistency (SDCM) | MacAdam step 3 |
| Warranty | 7 Years |



This luminaire contains built-in LED lamps

The lamps cannot be changed in the luminaire.

874/2012



Sensor luminaires turn on for 4 minutes after detecting movement. A different time can be set for large orders.

REWARDING BRIGHTNESS

Item specifications (part A)


| Description | Item code | Type | Input | W | Lm | Lm/W | CRI (typ.) | UGR | Pf | Ripple | Inrush current | B-16A Fuse |
|------------------------------------|--------------|-----------|----------|---|-----|------|------------|------|-----|--------|----------------|------------|
| Sensorlinea 75 LV-600 Lm 3000K 24° | 917203XX8714 | Incl. PSU | 220-240V | 8 | 600 | 75 | 83 | 17.1 | 0.6 | <3% | 20A 170µS | 50 |
| Sensorlinea 75 LV-600 Lm 4000K 24° | 917203XX9714 | Incl. PSU | 220-240V | 8 | 600 | 75 | 83 | 23.4 | 0.6 | <3% | 20A 170µS | 50 |
| Sensorlinea 75 LV-600 Lm 3000K 60° | 917203XX8814 | Incl. PSU | 220-240V | 8 | 600 | 75 | 83 | 17.1 | 0.6 | <3% | 20A 170µS | 50 |
| Sensorlinea 75 LV-600 Lm 4000K 60° | 917203XX9814 | Incl. PSU | 220-240V | 8 | 600 | 75 | 83 | 23.4 | 0.6 | <3% | 20A 170µS | 50 |

Item specifications (part B)

| Description | Safety class | Energy class | Weight | Dimensions single carton | Quantity per carton | Expected lifespan (25°C) | | |
|------------------------------------|--------------|--------------|--------|--------------------------|---------------------|--------------------------|-------------|------------|
| | | | | | | L70B50 | L80B50 | L90B50 |
| Sensorlinea 75 LV-600 Lm 3000K 24° | II | A | 262 gr | 105x105x105 mm | 45 pcs | 282.168 hrs | 178.352 hrs | 87.206 hrs |
| Sensorlinea 75 LV-600 Lm 4000K 24° | II | A | 262 gr | 105x105x105 mm | 45 pcs | 282.168 hrs | 178.352 hrs | 87.206 hrs |
| Sensorlinea 75 LV-600 Lm 3000K 60° | II | A | 262 gr | 105x105x105 mm | 45 pcs | 282.168 hrs | 178.352 hrs | 87.206 hrs |
| Sensorlinea 75 LV-600 Lm 4000K 60° | II | A | 262 gr | 105x105x105 mm | 45 pcs | 282.168 hrs | 178.352 hrs | 87.206 hrs |

All values are measured at 230V (+/- 7%).

Dimensions



Detection area

